



Servolight S1 *SuperTec*

Extended coverage flexible thin set mortar

- new mortar generation
- up to 30 % increased coverage than standard thin set
- for all approved substrates and covering materials
- improved flexural strength
- non sag mortar for large format tile
- neutral mortar color
- easy application
- excellent non-sag characteristics
- interior and exterior applications
- chlorinebased swimming pools
- 0,0 g/L VOC

Coverage

depends on substrate condition and other factors.

3 mm (TKB C3) approx. 0,7 kg/m²

4 mm (TKB C1) approx. 0,9 kg/m²

6 mm (TKB C2) approx. 1,8 kg/m²

Coverage is approximate and is given for estimating purposes only. It may vary according to substrate conditions and other factors.

Okalift
SuperChange

C2 TE-S1



54x 15-kg-paper bags

ANSI A 118.4



Servolight S2 *SuperTec*

Extended coverage flexible thin set mortar

- approx. 30 % higher area coverage
- self curing
- very high formability, flexibility according to EN 12 002 > 5 mm
- extremely light processing
- very high stability
- very high shear resistance
- excellent non-sag characteristics
- interior, exterior installation and submerged applications improved flexural strength for extreme large format, thin tiles
- 0,0 g/L VOC

Coverage

3 mm (TKB C3) approx. 0,7 kg/m²

4 mm (TKB C1) approx. 0,9 kg/m²

6 mm (TKB C2) approx. 1,3 kg/m²

8 mm (TKB C4 or bigger) approx. 1,8 kg/m²

Okalift
SuperChange

C2 TE-S2



54x 15-kg-paper bags

50x 3-kg-paper bags

ANSI A 118.4